

RZWS

Size: **25, 45, 90 cm**
Flow: **0.9 l/min or 1.9 l/min**

FEATURES

- Built-in Hunter Swing Joint for direct installation to ½" PVC fitting
- Hunter pressure-compensating bubbler for precise watering
- Pre-assembled watering system for fast installation
- Patented StrataRoot™ baffles divert water to root zone while adding strength to the unit
- Vandal-proof locking cap

FACTORY INSTALLED OPTIONS

- Check valve
- Locking reclaimed purple cap

USER INSTALLED OPTIONS

- Fabric sleeve that helps prevent soil intrusion in sandy areas for 45 cm and 90 cm models (P/N RZWS-SLEEVE)
- Replacement cap for 45 and 90 cm models (P/N 913300SP)
- Locking reclaimed purple cap for 45 and 90 cm models (P/N 913301SP)
- Reclaimed water purple cap for 25 cm (P/N RZWS10-RCC)

OPERATING SPECIFICATIONS

- Bubbler flow rates: 0.9 l/min or 1.9 l/min
- Recommended pressure range: 1.0 to 4.8 bar; 100 to 480 kPa



RZWS-10
Diameter: 5.1 cm
Length: 25 cm

RZWS-18
Tube Diameter: 7.6 cm
Cap Diameter: 12 cm
Length: 45 cm

RZWS-36
Tube Diameter: 7.6 cm
Cap Diameter: 12 cm
Length: 90 cm

RZWS patented StrataRoot™ baffles



Reclaimed models available
Add **-R** to model number

RZWS – SPECIFICATION BUILDER: Order 1 + 2 + 3

1 Model	2 Bubbler Flow Rate	3 Options
RZWS-10 = 25 cm Root Zone Watering System	25 = 0.9 l/min	(blank) = No option
RZWS-18 = 45 cm Root Zone Watering System	50 = 1.9 l/min	CV = Check valve
RZWS-36 = 90 cm Root Zone Watering System	(blank) = No bubbler or swing joint	R = Reclaimed cap
		CV-R = Check valve with reclaimed cap

Examples:

RZWS-18 - 25 - CV = 45 cm Root Zone Watering System at 0.9 l/min, with check valve
 RZWS-10 - 50 - R = 25 cm Root Zone Watering System at 1.9 l/min, with reclaimed cap
 RZWS-36 - 25 - CV-R = 90 cm Root Zone Watering System at 0.9 l/min, with check valve and reclaimed cap

ADDITIONAL OPTIONS (SPECIFY SEPARATELY)

RZWS-SLEEVE = Field-installed sleeve made from filter fabric