

1" PGV AND PGV JAR-TOP



These versatile and robust valves offer simple serviceability.

KEY BENEFITS

- External/internal manual bleed allows for quick and easy activation at the valve
- Double-beaded diaphragm seal design ensures leak-free performance
- Captive bonnet screws eliminate the possibility of lost parts during disassembly
- Triple-tool bonnet screws are compatible with standard or Phillips screwdrivers as well as a nut driver
- Jar-top models provide easy access without tools
- Encapsulated solenoid with captive plunger used on every Hunter valve provides hassle-free service
- Flow control maximises efficiency and prolongs the life of the system

USER-INSTALLED OPTIONS

- Accu Sync™ Pressure Regulator at the valve*
- DC-Latching Solenoid for battery-operated controllers (P/N 458200)

FACTORY-INSTALLED OPTIONS

- LS: Valve without solenoid
- DC: DC-Latching Solenoid for battery-operated controllers
- JT: Jar-top models

OPERATING SPECIFICATIONS

- Flow: 0.05 to 9 m³/hr; 0.7 to 150 l/min
- Recommended pressure range: 1.5 to 10 bar; 150 to 1000 kPa
- Temperature rating: 66°C
- Warranty period: 2 years

SOLENOID SPECIFICATIONS

- 24 VAC solenoid
 - 350 mA inrush, 190 mA holding, 60 Hz
 - 370 mA inrush, 210 mA holding, 50 Hz

- Accu Sync product information



PGV-100G
Inlet diameter: 1" (25 mm)
Height: 13 cm
Length: 11 cm
Width: 6 cm



PGV-101G
Inlet diameter: 1" (25 mm)
Height: 13 cm
Length: 11 cm
Width: 6 cm



PGV-100JT-G
Inlet diameter: 1" (25 mm)
Height: 14 cm
Length: 11 cm
Width: 8 cm



PGV-101JT-G
Inlet diameter: 1" (25 mm)
Height: 14 cm
Length: 11 cm
Width: 8 cm

Double-Beaded Diaphragm



AC Solenoid
(P/N 606800)
Two red wires



DC-Latching Solenoid
(P/N 458200)
One black (common) wire
and one red (station) wire

PGV - SPECIFICATION BUILDER : ORDER 1 + 2 + 3 + 4 + 5

1 Model	2 Standard Features	3 Feature Options	4 Options	5 User-Installed Options
PGV-100 = 1" (25 mm)	Globe valve, without flow control, threaded inlet/outlet	G-B = BSP female threaded inlet/outlet	DC = DC-Latching Solenoid for battery-operated controllers	AS-ADJ = Accu Sync adjustable
PGV-101 = 1" (25 mm)	Globe valve, with flow control, threaded inlet/outlet	MM-B = BSP male threaded inlet/outlet	LS = Less solenoid	458200 = DC-Latching Solenoid for battery-operated controllers 269205 = Reclaimed flow control handle LIT-700 = Reclaimed ID tag

Example:

PGV-101-G-B-DC = 1" (25 mm) PGV globe valve, with flow control, with female BSP inlet and outlet, with DC-Latching Solenoid

PGV JAR-TOP - SPECIFICATION BUILDER : ORDER 1 + 2 + 3 + 4 + 5

1 Model	2 Standard Features	3 Feature Options	4 Options	5 User-Installed Options
PGV-100-JT = 1" (25 mm)	Globe valve, jar-top bonnet, without flow control, threaded inlet/outlet	G-B = BSP female threaded inlet/outlet	DC = DC-Latching Solenoid for battery-operated controllers	AS-ADJ = Accu Sync adjustable
PGV-101-JT = 1" (25 mm)	Globe valve, jar-top bonnet, with flow control, threaded inlet/outlet	MM-B = BSP male threaded inlet/outlet	LS = Less solenoid	458200 = DC-Latching Solenoid for battery-operated controllers 269205 = Reclaimed flow control handle LIT-700 = Reclaimed ID tag

Example:

PGV-101-JT-MM-B-DC = 1" (25 mm) PGV globe valve, with jar-top bonnet, with flow control, with male BSP inlet and outlet, with DC-Latching Solenoid

1" (25 MM) PGV VALVE	
Flow m ³ /hr	Pressure Loss bar
0.3	0.08
1.0	0.11
2.5	0.13
3.5	0.16
4.5	0.23
5.5	0.43
6.5	0.62
8.0	1.10
9.0	1.48

1" (25 MM) PGV VALVE	
Flow l/min	Pressure Loss kPa
4	8
20	11
40	13
55	16
75	23
95	43
115	62
135	110
150	148

PGV-100G Installed



Captive Bonnet Bolts

