



The MP Rotator and The MPR40: The Partnership that Performs.



From our work with the revolutionary MP Rotator evolved the origins of a great idea. To maximize

the results of this multi-stream rotor, we pursued the next logical step. Introducing the MPR40—Calibrated at a consistent 40 PSI, it is designed to provide optimal performance when combined with the MP Rotator.

Together, the two are a true blend of technology and performance. In fact, the MPR40 is the only product of its kind. Discover the MPR40. Paired with the MP Rotator, it's a partnership that performs.





The MPR40 Sprinkler Body

Models

MPR40-00 - Shrub

MPR40-04-CV - 4 Pop-up (10 cm)

MPR40-06-CV - 6" Pop-up (15 cm)

MPR40-12-CV - 12" Pop-up (30 cm)

Dimensions

- · Overall height: MPR40-04-CV - 5%" (15.5 cm) $MPR40-06-CV - 8\frac{3}{4}$ " (22.5 cm) MPR40-12-CV - 16%" (41 cm)
- ½" female inlet NPT
- Exposed diameter: 21/4" (5.7 cm)

Operating Specifications

- Recommended pressure range: 15 to 100 PSI (1.0 to 6.9 bars; 103 to 689 kPa)
- Flow-by: 0 at 10 PSI (0.7 bars; 68 kPa) or greater; 0.1 GPM (0.02 m³/hr; 0.4 l/min) otherwise
- Check height: Up to 14' (4.3 m) elevation change

Options Available

- Field-installed black rubber cover (part # 469805)
- Field-installed reclaimed water identification snap-on cover (part # PROSRCCAP)
- Field-installed reclaimed water identification body cap (part # 458545)
- Field-installed vandal-proof cap (part # INST-VPC)



What Makes Hunter Sprinklers the Easiest to Adjust?

Our new two-piece ratchet design—with independent ratcheting ring—facilitates quicker, more precise sprinkler head adjustment. With its tough-as-nails, abrasion resistant, high impact material, it withstands any impact in higher pressure systems. Incredibly dirt tolerant, too. What more can we say?


The Wiper Seal that Works

The MPR40's pressure activated, multifunction wiper seal has been designed to reduce flow-by. The zero flush seal gives you surefire operation at low pressures and enables more sprinkler heads on the same zone. The wiper seal is designed to grip the riser when operating and keep debris out of the seal when retracted. No more body cap leaks



Built-in regulator set at 40 PSI • New easy-toidentify gray cap • Factory-installed drain check valve


MPR40 Optimal Performance



SPECIFICATION GUIDE EXAMPLE: MPR40 CV - MP200090 POP-UP HEIGHT OPTIONS MP ROTATORS MPR40 = MPR40 (Includes factory-**00** = Shrub CV = Factory-installed See MP Rotator Specification Guide installed 40 PSI pressure regulator) 04 = 4" Pop-up check valve (Pop-up 06 = 6" Pop-up models only) for details



Hunter Industries Incorporated 1940 Diamond Street, San Marcos, California 92078 www.HunterIndustries.com • www.MPRotator.com



Shrub model not shown.

