

HIDRA, AMBO (6/4")

HIDRA - 6/4", výsečové a kruhové provedení, dvě trysky



tryska	tlak		dostřik	průtok			PR
	[Bar]	[kPa]		[m³/h]	[l/min]	[l/s]	
12 a 5 mm	2,0	200	20,0	9,12	152,0	2,53	46
	3,0	300	24,0	10,92	182,0	3,03	38
	4,0	400	27,0	12,66	211,0	3,52	35
	5,0	500	30,0	14,16	236,0	3,93	31
14 a 5 mm	2,0	200	21,0	11,70	195,0	3,25	53
	3,0	300	25,0	14,34	239,0	3,98	46
	4,0	400	29,0	16,62	277,0	4,62	40
	5,0	500	31,0	18,54	309,0	5,15	39
16 a 5 mm	2,0	200	22,0	14,82	247,0	4,12	61
	3,0	300	26,0	18,18	303,0	5,05	54
	4,0	400	30,0	21,06	351,0	5,85	47
	5,0	500	33,0	23,46	391,0	6,52	43

HIDRA - 6/4", kruhové provedení, dvě trysky

tryska	tlak		dostřik	průtok			PR
	[Bar]	[kPa]		[m³/h]	[l/min]	[l/s]	
12 a 5 mm	2,0	200	20,0	9,12	152,0	2,53	23
	3,0	300	24,0	10,92	182,0	3,03	19
	4,0	400	27,0	12,66	211,0	3,52	17
	5,0	500	30,0	14,16	236,0	3,93	16
14 a 5 mm	2,0	200	21,0	11,70	195,0	3,25	27
	3,0	300	25,0	14,34	239,0	3,98	23
	4,0	400	29,0	16,62	277,0	4,62	20
	5,0	500	31,0	18,54	309,0	5,15	19
16 a 5 mm	2,0	200	22,0	14,82	247,0	4,12	31
	3,0	300	26,0	18,18	303,0	5,05	27
	4,0	400	30,0	21,06	351,0	5,85	23
	5,0	500	33,0	23,46	391,0	6,52	22

AMBO - 6/4", kruhové provedení, dvě trysky

tryska	tlak		dostřik	průtok			PR
	[Bar]	[kPa]		[m³/h]	[l/min]	[l/s]	
12 a 7 mm	2,0	200	19,5	10,14	169,0	2,82	27
	3,0	300	22,0	12,42	207,0	3,45	26
	4,0	400	25,0	14,34	239,0	3,98	23
	5,0	500	27,5	16,14	269,0	4,48	21
14 a 7 mm	3,0	300	20,5	12,90	215,0	3,58	31
	4,0	400	23,5	15,84	264,0	4,40	29
	5,0	500	26,0	18,30	305,0	5,08	27
	6,0	600	28,5	20,52	342,0	5,70	25
16 a 7 mm	3,0	300	21,0	16,02	267,0	4,45	36
	4,0	400	24,0	19,68	328,0	5,47	34
	5,0	500	26,5	22,74	379,0	6,32	32
	6,0	600	29,0	24,84	414,0	6,90	30



Poznámka:

- uvedené srážkové výšky (PR) pro výsečové postřikovače jsou počítány pro čtvercový spon a výseč 180°
- uvedené srážkové výšky (PR) pro celokruhové postřikovače jsou počítány pro čtvercový spon a výseč 360°